

Alfa Laval AXP52 AN

Fusion-bonded plate heat exchanger for extreme high-pressure applications

Alfa Laval AXP AN is specially designed for high-pressure applications with requirements for 100% stainless steel, for example, high pressure ammonia systems or compressor cooling.

Application

Designed for applications requiring 100% stainless steel.

Because of their high-pressure performance, they are particularly well-suited to CO_2 applications, such as transcritical gas cooling.

Benefits

- Tolerates extremely high operating pressures
- Compact
- Easy to install
- Self-cleaning
- Low level of service and maintenance is required
- All units are pressure and leak tested
- Gasket free
- Copper free

Design

The AlfaFusion filler material seals and holds the plates together at the contact points ensuring optimal heat transfer efficiency and pressure resistance. Using advanced design technologies and extensive verification guarantees the highest performance and longest possible service life.

AXP AN are fusion-bonded plate heat exchangers with thin external frames in carbon steel that are able to withstand extremely high operating pressures.

Always delivered with lifting lug for easy handling.



Examples of connections







External thread

Internal thread

Soldering



Welding

Technical Data

Standard materials

Cover plates	Stainless steel	
Connections	Stainless steel	
Plates	Stainless steel	
AlfaFusion filler	Stainless steel	
External frame	Carbon steel, Zinc electroplated	

Dimensions and weight¹

A measure (mm)	15 + (2.48 * n)
A measure (inches)	0.59 + (0.1 * n)
Weight (kg) ²	37.5 + (0.22 *n)
Weight (lb) ²	82.67 + (0.5 * n)

1. n = number of plates

2. Excluding connections


Standard data

Volume per channel, litres (gal)	0.095 (0.025)	
Max. particle size, mm (inch)	1.2 (0.047)	
Max. flowrate ¹ m ³ /h (gpm)	14 (62)	
Flow directions	Parallel	
Min. number of plates	6	
Max. number of plates	150	
1 Material E m $(a/(16/(4ft/a))/(a a proportion viola a it))$		

1. Water at 5 m/s (16.4 ft/s) (connection velocity)

Dimensional Drawing

mm (inches)



20 (0.79)

Design pressure and temperature

AXP52 AN - PED approved pressure/temperature graph



Designed for full vacuum.

Alfa Laval plate heat exchangers are available with a wide range of pressure vessel approvals. Please contact your Alfa Laval representative for more information.

NOTE: Values above are to be used as an indication. For exact values, please use the drawing generated by the Alfa Laval configurator or contact your local Alfa Laval representative.

CHE00051EN

How to contact Alfa Laval

Contact details for all countries are continually updated on our website. Please visit www.alfalaval.com to access the information direct.