



ERIS 5W 30



DESCRIPTION:

Synthetic engine oil 5W30 fuel economy

ERIS is high performance engine lubricant fluid formulated from a fully synthetic base and strictly selected additives in order to grant maximum engine performance.

The choice of fully synthetic base PAO (poly-alfa-olefine) provides outstanding thermal stability and oxidation resistance, as well as exceptional lubrication characteristics which assure friction reduction and consequently fuel consumption containment (fuel economy).

Thanks to its particular formulation ERIS 5W30 provides maximum performance over a wide working temperature range and prolonged oil change interval.

Particular low SAPS additives (low ashes, low sulphur and low phosphorus content) assures perfect engine and catalyst system cleanness and outstanding lubrication properties of ERIS contribute to significant mechanical parts wear reduction.

APPLICATIONS:

ERIS is high performance engine oil particularly formulated for DIESEL engines with catalyst and/or diesel particulate filter (DPF). ERIS is likewise indicated for dated vehicle fleets where SAE 5W30 oil is prescribed.

SPECIFICATIONS – HOMOLOGATIONS:

ACEA C4
 RENAULT RN 720
 MB 229.51

SECTORS OF APPLICATION:



PACKAGING

Bottle : 1lt

Tin : 18kg

Drum : 50kg

Barrel : 180kg

TYPE

PAO Oil: ✓

TECHNICAL SPECIFICATIONS

SAE : 5W / 30

ACEA : C4

Mercedes : MB 229.51

Viscosity DIN 51562 40°C : 68

Viscosity DIN 51562 100°C : 11,6

Viscosity index ISO 2909 : 164

Density 15°C DIN 51757 Kg/dm³ : 0,85

TBN mg KOH/g: 7

Minimum temperature for pumpability °C : -33

APPLICATIONS

Engine : ✓
