



PYXIS 5W 30



DESCRIPTION:

Synthetic engine oil 5W30 fuel economy

PYXIS is high performance engine lubricant fluid formulated from synthetic base and strictly selected additives in order to grant maximum engine performance.

The choice of synthetic base provides outstanding thermal stability and oxidation resistance, as well as exceptional lubrication characteristics which assure friction reduction and consequently fuel consumption containment (fuel economy).

Thanks to its particular formulation PYXIS 5W30 provides maximum performance over a wide working temperature range and prolonged oil change interval.

Particular low SAPS additivation (low ash content, low sulphur and low phosphorus level) assures perfect engine and catalyst system cleanness and outstanding lubrication properties of PYXIS contribute to significant mechanical parts wear reduction.

APPLICATIONS:

PYXIS is high performance engine oil particularly formulated for diesel and petrol vehicles with catalyst and/or diesel particulate filter (DPF). PYXIS is likewise indicated for dated vehicle fleets where SAE 5W30 oil is prescribed.

SPECIFICATIONS – HOMOLOGATIONS:

ACEA C2-08
 ACEA A5/B5-04
 ACEA A1/B1-04
 API SM/SN/CF
 RENAULT RN 0700
 PSA B71 2290

SECTORS OF APPLICATION:



PACKAGING

Bottle : 1lt

Tin : 18kg

Drum : 50kg

Barrel : 180kg

TYPE

Synthetic Base : ✓

TECHNICAL SPECIFICATIONS

SAE : 5W / 30

API : SM, SN, CF

ACEA : C2-08, A5/B5-04, A1/B1-04

Viscosity DIN 51562 40°C : 72

Viscosity DIN 51562 100°C : 12

Viscosity index ISO 2909 : 164

Density 15°C DIN 51757 Kg/dm³ : 0,84

TBN mg KOH/g: 7

APPLICATIONS

Engine : ✓
