



RACE SAE 10W/50



DESCRIPTION:

RACE - 4T SYNTHETIC MOTOR OIL SAE 10W/ 50

Peak performance 100% synthetic lubricant (PAO) for four-stroke engines. RACE's unique formulation ensures perfect lubrication under extreme conditions for all racing and conventional engines. RACE prevents carbon build-up on rings and pistons, ensuring fast heat dissipation and maximum engine power. RACE is perfectly compatible with oil-bathed clutch disks.


APPLICATIONS:

RACE è sviluppato per motori 4 tempi di alte prestazioni, che vanno dalle Superbike alle moto da cross. Ottimo anche per l'utilizzo su motoslitte.

SPECIFICATIONS – HOMOLOGATIONS:

API SM; JASO MA-2

SECTORS OF APPLICATION:



THIS PRODUCT IS RECOMMENDED BY:



PACKAGING

Bottle : 1 lt

Can : 5 kg

Tin : 18 kg

Drum : 50Kg

Barrel : 180Kg

TYPE

PAO Oil: ✓

TECHNICAL SPECIFICATIONS

SAE : 10W 50

API : SM

Viscosity DIN 51562 40°C : 108

Viscosity DIN 51562 100°C : 17,2

Viscosity index ISO 2909 : 175

Density 15°C DIN 51757 Kg/dm³ : 0,86

TBN mg KOH/g: 8,3

Minimum temperature for pumpability °C : -30

APPLICATIONS

Engine : ✓
