



RACE SAE 5W/40



DESCRIPTION:

RACE - 4T SYNTHETIC MOTOR OIL SAE 05W/40

Peak performance 100% synthetic lubricant (PAO) for four-stroke engines. RACE's unique formulation ensures perfect lubrication under extreme conditions for all racing and conventional engines. RACE prevents carbon build-up on rings and pistons, ensuring fast heat dissipation and maximum engine power. RACE is perfectly compatible with oil-bathed clutch disks.


APPLICATIONS:

FOR RACE is fully synthetic multigrade engine oil formulated and developed for use in 4-stroke motorcycle engines

SPECIFICATIONS – HOMOLOGATIONS:

API SM; JASO MA-2

SECTORS OF APPLICATION:



THIS PRODUCT IS RECOMMENDED BY:



DAL BOSCO
MX TEAM & SCHOOL RACING



GASGAS
ITALIA



SHERCO



TRS
MOTORCYCLES

PACKAGING

Bottle : 1lt

Drum : 50Kg

Barrel : 180Kg

TYPE

PAO Oil: ✓

TECHNICAL SPECIFICATIONS

SAE : 5W 40

API : SM

Viscosity DIN 51562 40°C : 75

Viscosity DIN 51562 100°C : 13,2

Viscosity index ISO 2909 : 180

Density 15°C DIN 51757 Kg/dm³ : 0,85

TBN mg KOH/g: 8,3

Minimum temperature for pumpability °C : -30

APPLICATIONS

Engine : ✓
