



ROAD SAE 15W/50



DESCRIPTION:

ROAD is a synthetic super multigrade oil developed to meet the lubrication needs of the last generation motorcycles with 4-stroke engines.

ROAD ensures optimum engine lubrication even at high running temperatures. ROAD keeps the engine and the sparkplugs clean to offer highest efficiency and performance.

ROAD protects the engine from wear, prolonging the life of the moving parts; in particular the special extreme-pressure additives guarantee protection of the gears in the engine.

ROAD, thanks to the special formulation, allows easy starting even in very cold weather as well as reduced fuel consumption.

ROAD ensures perfect oil-bath clutch operation under any condition and duty, avoiding problems of clutch slip.

APPLICATIONS:

ROAD is a oil developed to meet the lubrication needs of the last generation motorcycles with 4-stroke engines.

SPECIFICATIONS – HOMOLOGATIONS:

API SM; JASO MA

SECTORS OF APPLICATION:



THIS PRODUCT IS RECOMMENDED BY:



PACKAGING

Bottle : 1 lt
Can : 5kg
Tin : 18kg
Drum : 50Kg
Barrel : 180Kg

TYPE

Synthetic Base : ✓

TECHNICAL SPECIFICATIONS

SAE : 5W 40
API : SL
Viscosity DIN 51562 40°C : 65
Viscosity DIN 51562 100°C : 10,5
Viscosity index ISO 2909 : 150
Density 15°C DIN 51757 Kg/dm3 : 0,85
TBN mg KOH/g: 8,3
Minimum temperature for pumpability °C : -25

APPLICATIONS

Engine : ✓
