



ROAD SAE 20W/50



DESCRIPTION:

ROAD is a synthetic super multigrade oil developed to meet the lubrication needs of the last generation motorcycles with 4-stroke engines.

ROAD is also formulated for use in car petrol engines, with or without superchargers.

ROAD ensures optimum engine lubrication even at high running temperatures. ROAD keeps the engine and the sparkplugs clean to offer highest efficiency and performance.

ROAD protects the engine from wear, prolonging the life of the moving parts; in particular the special extreme-pressure additives guarantee protection of the gears in the engine.

ROAD, thanks to the special formulation, allows easy starting even in very cold weather as well as reduced fuel consumption.

ROAD ensures perfect oil-bath clutch operation under any condition and duty, avoiding problems of clutch slip.

APPLICATIONS:

ROAD is a oil developed to meet the lubrication needs of the last generation motorcycles with 4-stroke engines.

SPECIFICATIONS – HOMOLOGATIONS:

API SJ; JASO MA-2

SECTORS OF APPLICATION:



THIS PRODUCT IS RECOMMENDED BY:



PACKAGING

Drum : 50Kg

Barrel : 180Kg

TYPE

Synthetic Base : ✓

TECHNICAL SPECIFICATIONS

SAE : 20W 50

API : SJ

Viscosity DIN 51562 40°C : 178

Viscosity DIN 51562 100°C : 19

Density 15°C DIN 51757 Kg/dm3 : 0,89

Minimum temperature for pumpability °C : -36

Flash point 2592°C : >230

APPLICATIONS

Engine : ✓
