



SPIKA PRO 30



DESCRIPTION:

SPIKA PRO, thanks to its particular formulation, assures superior lubricant features even on engines working under particularly heavy conditions.

Efficient additive and detergent package, as well as dispersant agents guarantees perfect cleanness of engine and elimination of carbon deposits.

SPIKA PRO has excellent anti-corrosive properties, which permit use of fuel with elevated acidity (as vegetal fuel).

Elevated content of alkaline additives (TBN) assures long change intervals, as well as strong protection against aggressive acid substances.

APPLICATIONS:

SPIKA PRO is high performance lubricant, particularly formulated for use on heavy vegetal fuel engines operating.

SPECIFICATIONS – HOMOLOGATIONS:

API CD
MIL L 2104 C

SECTORS OF APPLICATION:



PACKAGING

Tin : 18kg

Drum : 50kg

Barrel : 180kg

TYPE

Mineral Oil :

TECHNICAL SPECIFICATIONS

SAE Monograde : 30

API : CD

Viscosity DIN 51562 40°C : 100

Viscosity DIN 51562 100°C : 11

Density 15°C DIN 51757 Kg/dm³ : 0,90

TBN mg KOH/g: 12,5

Flash point 2592°C : > 200

Pour point ISO 3016 °C : -12

APPLICATIONS

Engine :

