



STRATOS PLUS 10W 40



DESCRIPTION:

STRATOS PLUS is a fully synthetic UHPD-Mid SAPS (low ash content, low sulphur and phosphorus level) engine oil suitable for all diesel engines as well as for new generation EURO 4 and EURO 5 engines, based on PAO (poly-alpha-olephines) technology developed to deliver fuel economy to heavy-duty commercial vehicle and satisfy the longest engine manufacturer's oil drain specifications and prolong maximally exchange intervals.

STRATOS PLUS was developed in order to satisfy most advanced requests of high performance engines even if operating in extreme conditions.

STRATOS PLUS consents considerable fuel savings and thus operating costs reduction due to use of ultimate synthetic oil technology.

It permits moreover to prolong oil change intervals stated from main vehicle constructors, with significant contribute to maintenance costs reduction.

STRATOS is synthetic product formulated for protection and preservation of the engine; precise dosage of technologically advance additives with high detergent properties assures cleanness of the engine and prevents building of carbon deposits on pistons and other engine parts. Ideal combination of anti wear additives slow considerably internal wear of cylinders and prolongs engine life reducing maintenance costs.

STRATOS PLUS assures perfect running of engine in huge temperature range granting excellent performance even on extremely low start temperatures.

The synthetic base oil and the SAE 10W-40 viscosity grade provide excellent low temperature oil flow properties to enable rapid lubrication after cold starting, when the majority of wear occurs.

Mid SAPS technology assures perfect filters and catalyst system functioning as well as considerable polluting emission reduction.

APPLICATIONS:

STRATOS PLUS 10W 40 is engine oil suitable for all diesel engines as well as for new generation.

SPECIFICATIONS – HOMOLOGATIONS:

API C14/CJ4-SN; ACEA E6/E7/E9/E4; MB 228.51, 228.31; MAN M 3575,3477; VOLVO VDS 4; MTU Type 3.1/2.1; CAT ECF 3; RVI RLD 3; Cummins 20081; SCANIA LDF 3; DEUTZ DQC IV-10LA

SECTORS OF APPLICATION:



THIS PRODUCT IS RECOMMENDED BY:



PACKAGING

Can : 5Kg

Tin : 18kg

Drum : 50Kg

Barrel : 180Kg

TYPE

PAO Oil: ✓

TECHNICAL SPECIFICATIONS

SAE : 10W 40

API : CI4 / CJ4-SN

ACEA : E4 / E6 / E7 / E9

Caterpillar : ECF 2, ECF 3

Man : M 3575 / 3477

Mercedes : 228.51, 228.31

Viscosity DIN 51562 40°C : 104

Viscosity DIN 51562 100°C : 14,8

Viscosity index ISO 2909 : 148

Density 15°C DIN 51757 Kg/dm3 : 0,86

TBN mg KOH/g: 12.2

Pour point ISO 3016 °C : <-40

APPLICATIONS

Engine : ✓
