



VELA 5W 40



DESCRIPTION:

Synthetic engine oil 5W40 fuel economy

VELA is high performance engine lubricant formulated from synthetic base and strictly selected additives in order to grant maximum engine performance.

The choice of synthetic base assures to this product outstanding thermal stability and oxidation resistance, as well as exceptional lubrication characteristics which assure friction reduction and consequently fuel consumption containment (fuel economy).

Thanks to its particular formulation VELA 5W40 provides maximum performance over a wide working temperature range and prolonged oil change interval.

Special additives assures outstanding lubrication properties of VELA and contribute to significant mechanical parts improving engine efficiency.

APPLICATIONS:

VELA is high performance engine oil particularly formulated for diesel and petrol with catalyst cars and vans engines.

VELA is likewise indicated for dated vehicle fleets where SAE 5W40 oil is prescribed.

SPECIFICATIONS – HOMOLOGATIONS:

ACEA A3/B4

API SM/CF

MB 229.3

BMW Longlife 98

VW 502.00, 505.00

Porsche A 40

Renault RN 0700, 0710

SECTORS OF APPLICATION:



PACKAGING

Bottle : 1lt

Tin : 18kg

Drum : 50kg

Barrel : 180kg

TYPE

Synthetic Base : ✓

TECHNICAL SPECIFICATIONS

SAE : 5W / 40

API : SM, CF

ACEA : A3/B4

Mercedes : MB 229.3

Viscosity DIN 51562 40°C : 85

Viscosity DIN 51562 100°C : 14,3

Viscosity index ISO 2909 : 175

Density 15°C DIN 51757 Kg/dm3 : 0,85

Minimum temperature for pumpability °C : -35

APPLICATIONS

Engine : ✓
